



PowerEdge R6715

Versatility meets performance

Invest in a future-proof server for the data center that scales dynamically to push the limits of demanding applications, driving a faster return on investment.

Faster return when investing in the future of your business

The PowerEdge R6715 server is a single-socket optimized solution designed to deliver high performance, flexibility, and efficiency for a variety of applications. It is powered by 5th generation AMD EPYC™ processors and offers cutting-edge features that dynamically scale to push the upper limits of application performance.

Next level compute in your data center

Our partnership with AMD allows us to provide customer with a powerful 1U server that can handle a variety of multi-core workloads.

- The 5th generation AMD EPYC™ processor in the PowerEdge R6715 can deliver up to two-times better performance compared to previous generations.
- With dual OCP and DDR5 memory support, efficiently address I/O and richer storage needs in a single-socket design.

New configuration options for targeted workloads

The PowerEdge R6715 offers great flexibility with multiple configuration options to suit diverse customer needs.

- With support for up to 3 PCIe slots in a compact 1U form factor, it can easily adapt to different workload requirements.
- An ideal choice for businesses looking for a versatile server that can grow with their evolving needs.

Efficiency plus even greater rate of consolidation

Lower your total cost of ownership while reducing energy use and make the best use of existing data center space.

- SmartCooling design allows most configurations to be air-cooled.
- Improved heat sinks for better thermal performance.

Cyber Resilient Architecture for Zero Trust IT environment & operations

Security is integrated into every phase of the PowerEdge lifecycle, including protected supply chain and factory-to-site integrity assurance. The Silicon-based root of trust anchors end-to-end boot resilience while Multi-Factor Authentication (MFA) and role-based access controls safeguard trusted operations.

Increase efficiency and accelerate operations with autonomous collaboration

The Dell OpenManage systems management portfolio tames the complexity of managing and securing IT infrastructure. Using Dell Technologies' intuitive end-to-end tools, IT can deliver a secure, integrated experience by reducing process and information silos and focus on growing the business. The Dell OpenManage portfolio is the key to your innovation engine, unlocking the tools and automation that help you scale, manage, and protect your technology environment

Sustainability

From recycled materials in our products and packaging, to thoughtful, innovative options for energy efficiency, the PowerEdge portfolio is designed to make, deliver, and recycle products to help reduce the carbon footprint and lower your operation costs. We even make it easy to retire legacy systems responsibly with Dell Technologies.

PowerEdge R6715

Highest density per core ideal for:

- Virtualization with lower licensing cost
- Data Analytics

Rest easier with Dell Technologies Services

Maximize your PowerEdge Servers with comprehensive services designed to meet you wherever you are. Accelerate time to value in achieving high AI use cases with Professional Services for AI, choose from tailored deployment options with the ProDeploy Suite, receive proactive and predictive support with our ProSupport Suite, and so much more with our services available across 170 locations and backed by our 60K+ employees and partners.

*Feature available in second half of 2025. Please refer to the product configurator page on Dell.com to confirm feature availability.

Feature	Technical Specifications
Processor	One 5th Generation AMD EPYC 9005 Series processor with up to 160 cores per processor
Memory	• 24 DDR5 DIMM slots, supports RDIMM 6 TB max, speeds up to 5200 MT/s • Supports registered ECC DDR5 DIMMs only
Storage controllers	• Internal Controllers (RAID): PERC H365i, H965i, H975i • Internal Boot: Boot Optimized Storage Subsystem (BOSS-N1 DC-MHS) • External HBAs (non-RAID): HBA465e
Drive Bays	Front bays: • 4 x 3.5-inch SAS/SATA • 8 x 2.5-inch Universal or U.2 / 10 x 2.5-inch SAS/SATA • 10 x 2.5-inch with 4 x Universal • 16 x EDSFF E3.S Gen5 NVMe drives • 20 x EDSFF E3.S + Rear 2 x EDSFF E3.S
Power Supplies	• Platinum 800W, 1100W • Titanium: 800W, 1100W, 1500W, 1500W 277Vac & HVDC*, 1800W* • Telco: 1400W -48VDC
Cooling Options	Air cooling, Direct Liquid Cooling (DLC)
Fans	• Up to four sets (dual fan module) hot plug fans
Dimensions	• Height – 42.8 mm (1.68 inches) • Width – 482.0 mm (18.97 inches) • Depth – 816.921 mm (32.16 inches) with bezel – 815.141 mm (32.09 inches) without bezel
Form Factor	1 U rack server
Embedded Management	• iDRAC10 • iDRAC Direct • iDRAC RESTful API with Redfish • Racadm CLI • Quick Sync 2 wireless module
Bezel	Optional metal bezel
OpenManage Console	• OpenManage Enterprise (OME) • OME Power Manager • OME Services • OME Update Manager • OME APEX AIOps Observability • OME Integration for VMware vCenter (with VMware Aria Operations) • OME Integration for Microsoft System Center • OpenManage Integration for Windows Admin Center
Mobility	N/A
Tools	IPMI
Integrations and Connections	OpenManage Integrations • Redhat Ansible Collections • Terraform Providers
Change Management	• Dell Repository Manager • Dell System Update • Enterprise Catalogs • Server Update Utility (SUU)
Security	• AMD Secure Encrypted Virtualization (SEV) • AMD Secure Memory Encryption (SME) • Cryptographically signed firmware • Data at Rest Encryption (SED with local or external key management) • Secure Boot • Secured Component Verification (Hardware integrity check) • Secure Erase • Silicon Root of Trust • System Lockdown • TPM 2.0 FIPS, CC-TCG certified • Chassis Intrusion Detection
GPU Options	Up to 3 x 75W SW

Feature	Technical Specifications	
Ports	Front Ports 1 x USB 2.0 Type-A (optional LCP KVM) 1 x USB 2.0 Type-C (HOST/BMC Direct) 1 x MiniDisplay port (optional LCP KVM)	Rear Ports - Two USB 3.1 Type-A 1 x VGA 1 Gb dedicated BMC Ethernet port
	Internal Port 1 x USB 3.1 Type-A	
PCIe	Up to three PCIe slots (x16 connector) - Slot 1: 1 x16 Gen5 Full Height or Low Profile - Slot 2: 1 x16 Gen5 Low Profile or 1 x16 OCP3.0 - Slot 4: 1 x16 Gen5 Full Height or Low profile	
Gen5 PCIe slots	3	
OCP network options	2 x OCP card 3.0 (optional) and 1GbE, 10GbE, 25GbE, 100GbE and 400GbE - Slot 2: 1 x16 Gen5 OCP 3.0 - Slot 5: 1 x16 Gen5 OCP 3.0	
Embedded NIC	1 Gb dedicated BMC Ethernet port	
PCIe Add-in Card (AIC) NIC	100 GbE and 400GbE; NDR VPI (400GbE); FC 32	
Operating System and Hypervisors	- Canonical Ubuntu Server LTS - Microsoft Windows Server with Hyper-V - Red Hat Enterprise Linux - VMware ESXi - SUSE Linux Enterprise Server For specifications and interoperability details, see Dell.com/OSsupport .	
OEM-ready version available	From bezel to BIOS to packaging, your servers can look and feel as if they were designed and built by you. For more information, visit Dell.com/OEM .	

Note: From bezel to BIOS to packaging, your servers can look and feel as if they were designed and built by you with our OEMR platforms, while XL platforms provide extended transitions and stability for OEM Solutions customers. For more information, visit Dell.com -> Solutions -> OEM Solutions.

APEX on Demand

APEX Flex on Demand Acquire the technology you need to support your changing business with payments that scale to match actual usage. For more information, visit www.delltechnologies.com/en-us/payment-solutions/flexible-consumption/flex-on-demand.htm.

Discover more about PowerEdge servers



Learn more about services for PowerEdge servers



Learn more about our systems management solutions



Search our Resource Library



Follow PowerEdge servers on X (formerly Twitter)



Contact a Dell Technologies Expert for [Sales](#) or [Support](#)