

Specification Sheet



PowerEdge R770

Drive efficiency in your datacenter through maximum performance with optimized power.

Boost Datacenter Efficiencies and Performance

The Dell PowerEdge R770 is a 2U, dual-socket rack server designed for high performance computing with optimal power efficiency and balanced performance to boost your data center productivity. It balances advanced computing power with virtualization, artificial intelligence inferencing, cloud-native applications, hyperscale workloads, and scale out databases.

Purpose-built for enterprise and scalable infrastructures, the PowerEdge R770 offers standardization that easily integrates into existing environments, equipped with two Intel® Xeon® 6 processors with E-cores and P-cores it offers up to 1.69x better performance per watt than previous models, improving power efficiency and increasing rack density. The addition of GPU support further amplifies computational power, ensuring high performance with lower energy use.

These servers are available in rear I/O hot aisle and front I/O cold aisle configurations. The front I/O cold aisle improves serviceability, reduces maintenance time, and enhances efficiency, reliability, and uptime, supporting your sustainability goals by optimizing cooling and energy use. It also features Dell's Smart Power and Cooling Technology, optimized for air cooling to significantly reduce energy consumption, contributing to long-term operational savings.

Cyber Resilient Architecture for Zero Trust IT environment & operations

Security is integrated into every phase of the PowerEdge lifecycle, including protected supply chain and factory-to-site integrity assurance. The Silicon-based root of trust anchors end-to-end boot resilience while Multi-Factor Authentication (MFA) and role-based access controls safeguard trusted operations.

Increase efficiency and accelerate operations with autonomous collaboration

The Dell OpenManage systems management portfolio tames the complexity of managing and securing IT infrastructure. Using Dell Technologies' intuitive end-to-end tools, IT can deliver a secure, integrated experience by reducing process and information silos in order to focus on growing the business. The Dell OpenManage portfolio is the key to your innovation engine, unlocking the tools and automation that help you scale, manage, and protect your technology environment.

Sustainability

From recycled materials in our products and packaging, to thoughtful, innovative options for energy efficiency, the PowerEdge portfolio is designed to make, deliver, and recycle products to help reduce the carbon footprint and lower your operation costs. We even make it easy to retire legacy systems responsibly with Dell Technologies.

Rest easier with Dell Technologies Services

Maximize your PowerEdge Servers with comprehensive services designed to meet you wherever you are. Accelerate time to value in achieving high AI use cases with Professional Services for AI, choose from tailored deployment options with the ProDeploy Suite, receive proactive and predictive support with our ProSupport Suite, and so much more with our services available across 170 locations and backed by our 60K+ employees and partners.

PowerEdge R770

The Dell PowerEdge R770 is powered by Intel Xeon 6 Processors, DDR5 Memory, NVMe BOSS, Energy Star compliant, advanced cooling for cloud environments. Ideal for:

- Virtualization
- Artificial Intelligence Inferencing
- · Cloud-native applications
- Hyperscale workloads
- Scale out Databases

NOTE: This document provides a comprehensive list of product features. However, features marked with an asterisk (*) may not be available at launch but introduced in future updates. Please note that this document does not confirm the availability or release timeline of any feature. For the most accurate and up-to-date information on feature availability, please refer to the product configurator page on dell.com.

Feature	Technical Specifications		
Processor	Two Intel Xeon 6 Processors with up to 144 E-cores or 86 P-ce	ores per processor	
Memory	 32 DDR5 DIMM slots, supports RDIMM 8 TB max, speeds up to 6400 MT/s Supports registered ECC DDR5 DIMMs only 		
Storage controllers	 Internal Boot: Boot Optimized Storage Subsystem (BOSS-N1 DC-MHS): HWRAID 1, 2 x M.2 NVMe SSDs or M.2 Interposer board (DC-MHS): 2 x M.2 NVMe SSDs or USB Internal controllers: Front PERC H965i, Front PERC H975i, Front PERC H365i 		
Front and Rear Bays	 No backplane configuration Up to 8 x EDSFF E3.S Gen5 NVMe max 122.88 TB also comes with FIO configuration Up to 16 x EDSFF E3.S Gen5 NVMe max 245.76 TB also comes with FIO configuration Up to 32 x EDSFF E3.S Gen5 NVMe max 489.6 TB Up to 8 x 2.5 inch SAS/SATA/NVMe max 122.88 TB Up to 8 x 2.5-inch Universal max 245.6 TB Up to 16 x 2.5 inch SAS/SATA max 61.44 TB Up to 24 x 2.5 inch SAS/SATA max 92.16 TB Up to 16 x 2.5 inch SAS/SATA + 8 x 2.5-inch NVME) max 92.16 TB Up to 40 x EDSFF E3.S Gen5 NVMe max 61.4 TB Up to 4 x EDSFF E3.S Gen5 NVMe max 61.2 TB on the rear 		
Hot swap Power Supplies	 800 W Platinum 100—240 VAC or 240 VDC 1100 W Platinium 100—240 VAC or 240 VDC 1500 W Titanium 100—240 VAC or 240 VDC 1100 W Titanium 100—240 VAC or 240 VDC 3200 W Titanium 200—240 VAC or 240 VDC 800 W Titanium 100—240 VAC or 240 VDC 3200 W 277 VAC and 336 HVDC Titanium* 1400 W -48VDC 60mm* 1500 W 277 VAC and 336 HVDC Titanium* 2400 W Titanium 100—240 VAC or 240 VDC* 1800 W HLAC Titanium 200—240 VAC or 240 VDC* 		
Cooling Options	Air cooling and Direct Liquid Cooling		
Fans	Note: DLC is a rack solution and requires rack manifolds and a cooling distribution unit (CDU) to operate. • High performance Silver (HPR SLVR) fans/High performance Gold (HPR GOLD) fans • Up to 6 hot swappable fans		
Dimensions and Weight	 Height – 86.8 mm (3.42 inches) Width – 482 mm (18.97 inches) Weight – 28.53 kg (62.89 pound) 	Depth (for rear I/O configuration) • 802.40 mm (31.59 inches) with bezel • 801.51 mm (31.56 inches) without bezel Depth (for front I/O configuration) • 814.52 mm (32.07 inches) without bezel Note: The front I/O configuration does not support the bezel.	
Form Factor	2U rack server	110to. 110 Holle #0 collingulation about hot support allo 2020.	
Embedded Management	iDRAC iDRAC Direct iDRAC RESTful API with Redfish RACADM CLI iDRAC Service Module (iSM) Quick Sync 2 wireless module NativeEdge Endpoint NativeEdge Orchestrator		
Bezel	Optional security bezel		
Security	Cryptographically signed firmware Data at Rest Encryption (SEDs with local or external key in Secure Boot Secured Component Verification (Hardware integrity check Silicon Root of Trust System Lockdown System Lockdown (requires iDRAC10 Enterprise or Datace Chassis Intrusion Detection TPM 2.0 FIPS, CC-TCG certified	k)	
Network options	4 x OCP NIC 3.0 cards (optional) and 1GbE, 10GbE, 25GbE, 100GbE and 400GbE* Slot 4 1 x 8 or 1 x 16 Gen5 OCP 3.0 Slot 10 1 x 8 or 1 x 16 OCP 3.0 Slot 34 1 x 16 Gen5 OCP 3.0 on front riser Slot 38 1 x 16 Gen 5 OCP 3.0 on front riser		
D000	Slot 34 1 x 4 BOSS		
BOSS	Slot 6 1 x 4 BOSS		

Feature	Technical Specifications				
Ports	Front Ports: 1 x USB 2.0 Type C port 1 x USB 2.0 Type A port (optional) 1 x Mini-DisplayPort (optional) 1 x DB9 Serial (with front I/O configuration)	Rear Ports: 1 x Dedicated ethernet port for iDRAC management 1 x VGA 2 x USB 3.1 Type A ports	Internal Ports: • 1 x USB 3.1 Type A port		
PCle	 1 x Dedicated ethernet port for iDRAC management Upto two PCle slots (x16 connectors) Slot 31 1 x 16 Gen5 Full Height - Half Length or Full Length on front Riser Slot 36 1 x 16 Gen5 Full Height - Half Length on front Riser Upto eight PCle slots (x8 and x16 connectors) Slot 1 1 x 8 Gen5 Full Height - Half Length Slot 2 1 x 16 Gen5 Dual Width Full Length or 1 x 8 Gen5 Full Height - Half Length Slot 3 1 x 16 Gen5 Full Height - Half Length or 1 x 16 Gen5 Low Profile Slot 4 1 x 16 Gen5 Full Height - Half Length or 1 x 8 Gen5 Full Height - Half Length or 1 x 8 or 1 x 16 OCP 3.0 Slot 5 2 x 16 Gen5 Full Height - Half Length or 1 x 8 Gen5 Full Height - Half Length Slot 7 1 x 16 Gen5 Full Height - Half Length or 1 x 8 Gen5 Full Height - Half Length Slot 8 1 x 16 Gen5 Full Height - Half Length or 1 x 8 Gen5 Full Height - Half Length Slot 9 1 x 16 Gen5 Full Height - Half Length or 1 x 8 Gen5 Full Height - Half Length Slot 9 1 x 16 Gen5 Full Height - Half Length or 1 x 8 Gen5 Full Height - Half Length 				
Operating System and Hypervisors	Canonical Ubuntu Server LTS Microsoft Windows Server with Hyper-V (P-Core only) Red Hat Enterprise Linux SUSE Linux Enterprise Server VMware ESXi For specifications and interoperability details, see Dell.com/OSsupport.				
OEM-ready version available	From bezel to BIOS to packaging, your servers can look and feel as if they were designed and built by you. For more information, visit Dell.com -> Solutions -> OEM Solutions.				

^{*}Feature not available at product launch in June 2025. Please refer to the product configurator page on Dell.com to confirm feature availability.

NOTE: From bezel to BIOS to packaging, your servers can look and feel as if they were designed and built by you with our OEMR platforms, while XL platforms provide extended transitions and stability for OEM Solutions customers. For more information, visit Dell.com -> Solutions -> OEM Solutions.

APEX Flex on Demand

Acquire the technology you need to support your changing business with payments that scale to match actual usage. For more information, visit https://www.delltechnologies.com/en-us/payment-solutions/flexible-consumption/flex-on-demand.htm.

Discover more about PowerEdge servers



Learn more about services for PowerEdge servers



Learn more about our systems management solutions



Search our Resource Library



Follow PowerEdge servers on X (formerly Twitter)



Contact a Dell Technologies Expert for Sales or Support

